

## Ürün Özellikleri

Diş normları : PG DIN 46320

: Metrik EN 60423

: NPT ANSI B1.20.1

: GAS ISO 228

Standart : DIN 89250

Sızdırmazlık : IP 56

Isıya dayanımı : -40° C +80° C

Hammadesi : Piriç (MS 58)



## IP-56 Caretta Piriç Gemi Buatları

Kod No	Malzeme Cinsi	Kablo Çapı "Ø"		Diyagram	Kutu
		Min	Max		Adet
RGB.05.576	1 RAKORLU BUAT	7,0	12,0		10,0
RGB.05.576 L	1 RAKORLU BUAT	10,0	14,0		10,0
RGB.05.577	2 RAKORLU BUAT	7,0	12,0		10,0
RGB.05.577 L	2 RAKORLU BUAT	10,0	14,0		10,0
RGB.05.585	2 RAKORLU BUAT	7,0	12,0		10,0
RGB.05.585 L	2 RAKORLU BUAT	10,0	14,0		10,0
RGB.05.578	2 RAKORLU BUAT	7,0	12,0		10,0
RGB.05.578 L	2 RAKORLU BUAT	10,0	14,0		10,0
RGB.05.579	3 RAKORLU BUAT	7,0	12,0		5,0
RGB.05.579 L	3 RAKORLU BUAT	10,0	14,0		5,0
RGB.05.580	4 RAKORLU BUAT	7,0	12,0		5,0
RGB.05.580 L	4 RAKORLU BUAT	10,0	14,0		5,0
RGB.05.581	5 RAKORLU BUAT	8,0	15,0		5,0
RGB.05.582	6 RAKORLU BUAT	8,0	15,0		5,0
RGB.05.583	7 RAKORLU BUAT	8,0	15,0		5,0
RGB.05.584	8 RAKORLU BUAT	8,0	15,0		5,0