

Ürün Özellikleri

Diş normları : TS EN 61386-22

Sıkıştırma Dayanım : Class 2

Darbeye Karşı Dayanım : Class 3

Isıya dayanımı : -15° C +60° C

Hammadesi : Galvaniz Çelik

Özellik : Esnek / Kendini toparlayan



Rex - Flex Galvaniz Çelik Spiral Borular

Anma Ölçüsü	Kod No	İç Çap "Ø"	Dış Çap "Ø"	Ambalaj
		mm	mm	1 Top/Mt.
7 mm- 1/4"	SPH.15.150	7,0	10,5	50,0
9 mm- 1/4"	SPH.15.151	9,0	12,0	50,0
11 mm- 3/8"	SPH.15.152	11,0	14,0	50,0
14 mm	SPH.15.153	14,0	17,0	50,0
16 mm- 1/2"	SPH.15.154	16,0	19,0	50,0
18 mm	SPH.15.155	18,0	21,0	50,0
21 mm- 3/4"	SPH.15.156	21,0	24,0	50,0
26 mm- 1	SPH.15.157	26,0	29,0	25,0
29 mm	SPH.15.158	29,0	33,0	25,0
32 mm	SPH.15.159	32,0	36,0	25,0
35 mm- 1-1/4	SPH.15.160	35,0	39,0	25,0
37 mm	SPH.15.161	37,0	41,0	25,0
40 mm- 1-1/2"	SPH.15.162	40,0	44,0	25,0
42 mm	SPH.15.163	42,0	46,0	25,0
45 mm	SPH.15.164	45,0	49,0	25,0
50 mm- 2"	SPH.15.165	50,0	54,0	25,0
65 mm- 2-1/2	SPH.15.166	65,0	70,0	25,0
75 mm- 3"	SPH.15.167	75,0	81,0	15,0
100 mm- 4"	SPH.15.168	100,0	108,0	10,0