

Ürün Özellikleri

Diş normları : PG DIN 46320

: Metrik EN 60423

: NPT ANSI B1.20.1

: GAS ISO 228

Sızdırmazlık : IP 68

Isıya dayanımı : -40° C +80° C

Hammadesi : Pirinç (MS 58) Nikel Kaplama



Waterproof Nikel Kablo Rakorları

Anma Ölçüsü	Kod No	Montaj Çap "Ø"	Diş Boyu	Kablo Çapı "Ø"		Kutu
		(mm)	(mm)	Min	Max	Adet
PG-7	REM.06.412	12,5	6,0	3,0	6,5	50,0
PG-9	REM.06.416	15,5	7,0	4,0	8,0	50,0
PG-11	REM.06.418	19,0	7,0	5,0	10,0	50,0
PG-13,5	REM.06.420	20,5	7,0	6,0	12,0	50,0
PG-16	REM.06.425	22,5	8,0	10,0	14,0	50,0
PG-21	REM.06.432	28,5	8,0	13,0	18,0	25,0
PØ-25	REM.06.433	32,0	9,0	18,0	22,0	25,0
PG-29	REM.06.440	37,5	10,0	18,0	25,0	20,0
PG-36	REM.06.450	47,0	10,0	24,0	32,0	10,0
PG-42	REM.06.456	55,0	12,0	30,0	38,0	10,0
PG-48	REM.06.463	60,0	14,0	34,0	44,0	10,0
PØ-55	REM.06.468	65,0	14,0	38,0	49,0	10,0
PØ-60	REM.06.473	70,0	15,0	40,0	52,0	10,0
PØ-70	REM.06.478	80,0	15,0	48,0	60,0	10,0
PØ-80	REM.06.483	90,0	16,0	59,0	71,0	10,0
PØ-90	REM.06.488	100,0	17,0	65,0	76,0	10,0
PØ-100	REM.06.493	110,0	18,0	65,0	76,0	10,0

Ürün Özellikleri

Diş normları : PG DIN 46320

: Metrik EN 60423

: NPT ANSI B1.20.1

: GAS ISO 228

Sızdırmazlık : IP 68

Isıya dayanımı : -40° C +80° C

Hammadesi : Pirinç (MS 58) Nikel Kaplama



Waterproof Nikel Kablo Rakorları

Anma Ölçüsü	Kod No	Montaj Çap "Ø"	Diş Boyu	Kablo Çapı "Ø"		Kutu
		(mm)	(mm)	Min	Max	Adet
M10x1,5	REM.06.010	12,0	6,0	3,0	6,5	50,0
M12x1,5	REM.06.012	12,0	6,0	3,0	6,5	50,0
M12x1,5	REM.06.013	12,0	6,0	4,0	8,0	50,0
M16x1,5	REM.06.016	16,0	7,0	4,0	8,0	50,0
M16x1,5	REM.06.017	16,0	7,0	5,0	10,0	50,0
M20x1,5	REM.06.020	20,0	8,0	6,0	12,0	25,0
M20x1,5	REM.06.021	20,0	8,0	10,0	14,0	25,0
M25x1,5	REM.06.025	25,0	8,0	10,0	14,0	25,0
M25x1,5 L	REM.06.026	25,0	8,0	10,0	16,0	25,0
M32x1,5	REM.06.032	32,0	9,0	13,0	18,0	25,0
M32x1,5	REM.06.033	32,0	9,0	18,0	25,0	25,0
M40x1,5	REM.06.040	40,0	10,0	18,0	25,0	20,0
M40x1,5	REM.06.041	40,0	10,0	22,0	32,0	20,0
M50x1,5	REM.06.050	50,0	10,0	22,0	32,0	20,0
M50x1,5	REM.06.051	50,0	10,0	30,0	38,0	10,0
M56x1,5	REM.06.056	56,0	12,0	30,0	38,0	10,0

Ürün Özellikleri

Diş normları : PG DIN 46320

: Metrik EN 60423

: NPT ANSI B1.20.1

: GAS ISO 228

Sızdırmazlık : IP 68

Isıya dayanımı : -40° C +80° C

Hammadesi : Pirinç (MS 58) Nikel Kaplama



Waterproof Nikel Kablo Rakorları

Anma Ölçüsü	Kod No	Montaj Çap "Ø"	Diş Boyu	Kablo Çapı "Ø"		Kutu
		(mm)	(mm)	Min	Max	Adet
M63x1,5	REM.06.062	63,0	14,0	30,0	38,0	10,0
M63x1,5	REM.06.063	63,0	14,0	34,0	44,0	10,0
M63X1,5	REM.06.062	63,0	14,0	40,0	52,0	10,0
M63x1,5	REM.06.064	63,0	14,0	48,0	56,0	10,0
M65x1,5	REM.06.065	65,0	14,0	38,0	49,0	10,0
M70x1,5	REM.06.070	70,0	14,0	40,0	52,0	10,0
M72x1,5	REM.06.072	72,0	16,0	40,0	52,0	10,0
M72x2	REM.06.073	72,0	16,0	48,0	60,0	10,0
M75x1,5	REM.06.075	75,0	16,0	48,0	60,0	10,0
M75x2	REM.06.076	75,0	16,0	48,0	60,0	10,0
M75x2	REM.06.077	75,0	16,0	59,0	71,0	10,0
M80x1,5	REM.06.080	80,0	18,0	48,0	60,0	10,0
M80x1,5	REM.06.081	80,0	18,0	59,0	71,0	10,0
M80x2	REM.06.082	80,0	18,0	59,0	71,0	10,0
M85x2	REM.06.085	85,0	22,0	59,0	71,0	10,0
M90x2	REM.06.090	90,0	22,0	59,0	71,0	10,0
M90x2	REM.06.091	90,0	22,0	65,0	76,0	10,0
M100x2	REM.06.100	100,0	22,0	65,0	76,0	10,0
M110x2	REM.06.110	110,0	25,0	65,0	76,0	10,0

Ürün Özellikleri

Diş normları : PG DIN 46320

: Metrik EN 60423

: NPT ANSI B1.20.1

: GAS ISO 228

Sızdırmazlık : IP 68

Isıya dayanımı : -40° C +80° C

Hammadesi : Pirinç (MS 58) Nikel Kaplama



Waterproof Nikel Kablo Rakorları

Anma Ölçüsü	Kod No	Montaj Çap "Ø"	Diş Boyu	Kablo Çapı "Ø"		Kutu
		(mm)	(mm)	Min	Max	Adet
1/4" Npt	REM.06.212	13,5	16,0	3,0	6,5	50,0
3/8" Npt	REM.06.215	17,0	16,0	3,0	6,5	50,0
3/8" Npt	REM.06.216	17,0	16,0	4,0	8,0	50,0
3/8" Npt	REM.06.217	17,0	16,0	5,0	10,0	50,0
1/2" Npt	REM.06.220	21,3	18,0	6,0	12,0	50,0
1/2" Npt	REM.06.221	21,3	18,0	10,0	14,0	50,0
3/4" Npt	REM.06.227	26,7	18,0	13,0	18,0	25,0
1" Npt	REM.06.232	33,6	20,0	13,0	18,0	25,0
1" Npt	REM.06.233	33,6	20,0	18,0	25,0	20,0
1-1/4" Npt	REM.06.240	42,2	20,0	18,0	25,0	10,0
1-1/4" Npt	REM.06.241	42,2	20,0	24,0	32,0	10,0
1-1/2" Npt	REM.06.250	48,1	20,0	24,0	32,0	10,0
2" Npt	REM.06.262	59,9	22,0	40,0	52,0	10,0
2" Npt	REM.06.263	59,9	22,0	34,0	44,0	10,0
2-1/2" Npt	REM.06.272	75,5	22,0	40,0	52,0	10,0
2-1/2" Npt	REM.06.276	75,5	22,0	48,0	60,0	10,0
3" Npt	REM.06.280	88,2	24,0	48,0	60,0	10,0
3" Npt	REM.06.285	88,2	24,0	59,0	71,0	10,0
3-1/2" Npt	REM.06.291	100,6	24,0	65,0	76,0	10,0
4" Npt	REM.06.292	113,3	24,0	59,0	71,0	10,0
4" Npt	REM.06.295	113,3	24,0	65,0	76,0	10,0