

Ürün Özellikleri

Diş normları : PG DIN 46320

: Metrik EN 60423

: NPT ANSI B1.20.1

: GAS ISO 228

Sızdırmazlık : IP 66, IP 68

Isıya dayanımı : -40° C +80° C

Hammadesi : Pirinç (MS 58) Nikel Kaplama



CW Serisi Exproof Zırlı Nikel Kablo Rakorları

| Anma Ölçüsü | Kod No | Montaj Çap "Ø" | Diş Boyu | A Kablo Çapı "Ø" | B Kablo Çapı "Ø" | | Kutu |
|-------------|-----------|----------------|----------|------------------|------------------|------|------|
| | | (mm) | (mm) | Max | Min | Max | Adet |
| M10x1,5 | CW.06.010 | 10,0 | 10,0 | 4,5 | 3,0 | 6,5 | 50,0 |
| M12x1,5 | CW.06.012 | 12,0 | 10,0 | 6,5 | 4,0 | 9,0 | 50,0 |
| M16x1,5 | CW.06.016 | 16,0 | 12,0 | 9,0 | 11,0 | 13,5 | 50,0 |
| M20x1,5 s | CW.06.019 | 20,0 | 12,0 | 13,0 | 15,0 | 20,0 | 50,0 |
| M20x1,5 | CW.06.020 | 20,0 | 12,0 | 15,0 | 17,0 | 22,0 | 50,0 |
| M20x1,5L | CW.06.021 | 20,0 | 12,0 | 17,0 | 17,0 | 22,0 | 50,0 |
| M25x1,5s | CW.06.024 | 25,0 | 12,0 | 19,0 | 20,0 | 27,0 | 50,0 |
| M25x1,5 | CW.06.025 | 25,0 | 12,0 | 19,0 | 22,0 | 30,0 | 50,0 |
| M25x1,5L | CW.06.026 | 25,0 | 12,0 | 22,0 | 20,0 | 27,0 | 25,0 |
| M32x1,5s | CW.06.031 | 32,0 | 12,0 | 26,0 | 26,0 | 33,0 | 25,0 |
| M32x1,5 | CW.06.032 | 32,0 | 12,0 | 27,0 | 28,0 | 37,0 | 25,0 |
| M32x1,5L | CW.06.033 | 32,0 | 12,0 | 30,0 | 28,0 | 37,0 | 25,0 |
| M40x1,5s | CW.06.039 | 40,0 | 15,0 | 32,0 | 31,0 | 40,0 | 20,0 |
| M40x1,5 | CW.06.040 | 40,0 | 15,0 | 33,0 | 36,0 | 45,0 | 20,0 |
| M40x1,5L | CW.06.041 | 40,0 | 15,0 | 37,0 | 36,0 | 45,0 | 20,0 |
| M50x1,5s | CW.06.049 | 50,0 | 15,0 | 44,0 | 43,0 | 54,0 | 15,0 |
| M50x1,5 | CW.06.050 | 50,0 | 15,0 | 45,0 | 49,0 | 59,0 | 15,0 |
| M50x1,5L | CW.06.051 | 50,0 | 15,0 | 49,0 | 49,0 | 59,0 | 15,0 |
| M63x1,5s | CW.06.062 | 63,0 | 15,0 | 54,0 | 58,0 | 64,0 | 10,0 |
| M63x1,5 | CW.06.063 | 63,0 | 15,0 | 56,0 | 60,0 | 69,0 | 10,0 |
| M63x1,5L | CW.06.064 | 63,0 | 15,0 | 64,0 | 60,0 | 72,0 | 10,0 |
| M75x1,5s | CW.06.074 | 75,0 | 16,0 | 64,0 | 61,0 | 72,0 | 5,0 |
| M75x1,5 | CW.06.075 | 75,0 | 16,0 | 68,0 | 65,0 | 78,0 | 5,0 |

Ürün Özellikleri

Diş normları : PG DIN 46320

: Metrik EN 60423

: NPT ANSI B1.20.1

: GAS ISO 228

Sızdırmazlık : IP 66, IP 68

Isıya dayanımı : -40° C +80° C

Hammadesi : Pirinç (MS 58) Nikel Kaplama



CW Serisi Exproof Zırlı Nikel Kablo Rakorları

| Anma Ölçüsü | Kod No | Montaj Çap "Ø" | Diş Boyu | A Kablo Çapı "Ø" | B Kablo Çapı "Ø" | | Kutu |
|-------------|-----------|----------------|----------|------------------|------------------|-------|------|
| | | (mm) | (mm) | Max | Min | Max | Adet |
| M80x2s | CW.06.079 | 80,0 | 16,0 | 69,0 | 65,0 | 78,0 | 4,0 |
| M80x2 | CW.06.080 | 80,0 | 16,0 | 72,0 | 73,0 | 83,0 | 4,0 |
| M90x2s | CW.06.089 | 90,0 | 18,0 | 78,0 | 73,0 | 83,0 | 2,0 |
| M90x2 | CW.06.090 | 90,0 | 18,0 | 78,0 | 77,0 | 89,0 | 2,0 |
| M90x2L | CW.06.091 | 90,0 | 18,0 | 82,0 | 86,0 | 95,0 | 2,0 |
| M100x2s | CW.06.099 | 100,0 | 20,0 | 83,0 | 77,0 | 89,0 | 1,0 |
| M100x2 | CW.06.100 | 100,0 | 22,0 | 89,0 | 86,0 | 98,0 | 1,0 |
| M110x2 | CW.06.110 | 110,0 | 22,0 | 98,0 | 95,0 | 110,0 | 1,0 |
| M118x2 | CW.06.118 | 118,0 | 22,0 | 110,0 | 115,0 | 130,0 | 1,0 |
| PG-7s | CW.06.410 | 12,5 | 10,0 | 4,5 | 3,0 | 6,5 | 50,0 |
| PG-7 | CW.06.412 | 12,5 | 10,0 | 6,5 | 4,0 | 9,0 | 50,0 |
| PG-9 | CW.06.416 | 15,5 | 12,0 | 9,0 | 11,0 | 13,5 | 50,0 |
| PG-13,5 | CW.06.419 | 20,5 | 12,0 | 13,0 | 15,0 | 20,0 | 50,0 |
| PG-16s | CW.06.420 | 22,5 | 12,0 | 15,0 | 17,0 | 22,0 | 50,0 |
| PG-16 | CW.06.421 | 22,5 | 12,0 | 17,0 | 17,0 | 22,0 | 50,0 |
| PG-21s | CW.06.424 | 28,5 | 12,0 | 19,0 | 20,0 | 27,0 | 50,0 |
| PG-21 | CW.06.425 | 28,5 | 12,0 | 19,0 | 22,0 | 30,0 | 50,0 |
| PG-21L | CW.06.426 | 28,5 | 12,0 | 22,0 | 20,0 | 27,0 | 25,0 |
| PG-29s | CW.06.431 | 37,5 | 12,0 | 26,0 | 26,0 | 33,0 | 25,0 |
| PG-29 | CW.06.432 | 37,5 | 12,0 | 27,0 | 28,0 | 37,0 | 25,0 |
| PG-29L | CW.06.433 | 37,5 | 12,0 | 30,0 | 28,0 | 37,0 | 25,0 |
| PG-36s | CW.06.439 | 47,0 | 15,0 | 32,0 | 31,0 | 40,0 | 20,0 |
| PG-36 | CW.06.440 | 47,0 | 15,0 | 33,0 | 36,0 | 45,0 | 20,0 |
| PG-36L | CW.06.441 | 47,0 | 15,0 | 37,0 | 36,0 | 45,0 | 20,0 |
| PG-36 | CW.06.449 | 47,0 | 15,0 | 44,0 | 43,0 | 54,0 | 15,0 |
| PG-42s | CW.06.450 | 55,0 | 15,0 | 45,0 | 49,0 | 59,0 | 15,0 |
| PG-42 | CW.06.451 | 55,0 | 15,0 | 49,0 | 49,0 | 59,0 | 15,0 |
| PG-48 | CW.06.462 | 60,0 | 15,0 | 54,0 | 58,0 | 64,0 | 10,0 |

Ürün Özellikleri

Diş normları : PG DIN 46320

: Metrik EN 60423

: NPT ANSI B1.20.1

: GAS ISO 228

Sızdırmazlık : IP 66, IP 68

Isıya dayanımı : -40° C +80° C

Hammadesi : Pirinç (MS 58) Nikel Kaplama



CW Serisi Exproof Zırlı Nikel Kablo Rakorları

| Anma Ölçüsü | Kod No | Montaj Çap "Ø" | Diş Boyu | A Kablo Çapı "Ø" | B Kablo Çapı "Ø" | | Kutu |
|-------------|-----------|----------------|----------|------------------|------------------|-------|------|
| | | (mm) | (mm) | Max | Min | Max | Adet |
| 1/8 Npt | CW.06.210 | 10,0 | 16,0 | 4,5 | 3,0 | 6,5 | 50,0 |
| 1/4"Npt | CW.06.212 | 13,5 | 16,0 | 6,5 | 4,0 | 9,0 | 50,0 |
| 3/8" Npt | CW.06.216 | 17,0 | 16,0 | 9,0 | 11,0 | 13,5 | 50,0 |
| 1/2"s Npt | CW.06.219 | 21,3 | 18,0 | 11,0 | 11,0 | 15,0 | 50,0 |
| 1/2" Npt | CW.06.220 | 21,3 | 18,0 | 13,0 | 15,0 | 20,0 | 50,0 |
| 1/2"L Npt | CW.06.221 | 21,3 | 18,0 | 15,0 | 17,0 | 22,0 | 50,0 |
| 3/4"sNpt | CW.06.224 | 26,7 | 18,0 | 17,0 | 17,0 | 22,0 | 50,0 |
| 3/4" Npt | CW.06.225 | 26,7 | 18,0 | 19,0 | 20,0 | 27,0 | 50,0 |
| 3/4"L Npt | CW.06.226 | 26,7 | 18,0 | 19,0 | 22,0 | 30,0 | 25,0 |
| 1"s Npt | CW.06.231 | 33,5 | 20,0 | 22,0 | 20,0 | 27,0 | 25,0 |
| 1" Npt | CW.06.232 | 33,5 | 20,0 | 26,0 | 26,0 | 33,0 | 25,0 |
| 1"L Npt | CW.06.233 | 33,5 | 20,0 | 27,0 | 28,0 | 37,0 | 25,0 |
| 1-1/4"s Npt | CW.06.239 | 42,2 | 20,0 | 30,0 | 28,0 | 37,0 | 20,0 |
| 1-1/4" Npt | CW.06.240 | 42,2 | 20,0 | 32,0 | 31,0 | 40,0 | 20,0 |
| 1-1/2sNpt | CW.06.241 | 48,1 | 20,0 | 33,0 | 36,0 | 45,0 | 20,0 |
| 1-1/2" Npt | CW.06.249 | 48,1 | 20,0 | 37,0 | 36,0 | 45,0 | 15,0 |
| 2"s Npt | CW.06.250 | 59,9 | 20,0 | 44,0 | 43,0 | 54,0 | 15,0 |
| 2" Npt | CW.06.251 | 59,9 | 20,0 | 45,0 | 49,0 | 59,0 | 15,0 |
| 2-1/4" Npt | CW.06.262 | 66,0 | 22,0 | 49,0 | 49,0 | 59,0 | 10,0 |
| 2-1/2"s Npt | CW.06.263 | 75,5 | 22,0 | 54,0 | 58,0 | 64,0 | 10,0 |
| 2-1/2" Npt | CW.06.264 | 75,5 | 22,0 | 56,0 | 60,0 | 69,0 | 10,0 |
| 2-1/2"L Npt | CW.06.274 | 75,5 | 22,0 | 64,0 | 61,0 | 72,0 | 5,0 |
| 2-3/4" Npt | CW.06.279 | 81,8 | 22,0 | 69,0 | 65,0 | 78,0 | 5,0 |
| 3"s Npt | CW.06.289 | 88,2 | 22,0 | 78,0 | 73,0 | 83,0 | 2,0 |
| 3" Npt | CW.06.290 | 88,2 | 22,0 | 78,0 | 77,0 | 89,0 | 2,0 |
| 3-3/4" Npt | CW.06.291 | 107,0 | 22,0 | 82,0 | 86,0 | 98,0 | 1,0 |
| 3-1/2"s Npt | CW.06.292 | 100,6 | 22,0 | 83,0 | 77,0 | 89,0 | 1,0 |
| 3-1/2" Npt | CW.06.293 | 100,6 | 22,0 | 89,0 | 86,0 | 98,0 | 1,0 |
| 4" Npt | CW.06.294 | 113,3 | 22,0 | 98,0 | 95,0 | 110,0 | 1,0 |
| 4-1/2" Npt | CW.06.295 | 126,0 | 22,0 | 110,0 | 115,0 | 130,0 | 1,0 |