

Ürün Özellikleri

Diş normları : PG DIN 46320

: Metrik EN 60423

: NPT ANSI B1.20.1

: GAS ISO 228

Sızdırmazlık : IP 66, IP 68

Isıya dayanımı : -40° C +80° C

Hammadesi : Paslanmaz Çelik 303 304 316 316L



CW Serisi Exproof Zırlı Paslanmaz Kablo Rakorları

Anma Ölçüsü	Kod No	Montaj Çap "Ø"	Diş Boyu	A Kablo Çapı "Ø"	B Kablo Çapı "Ø"		Kutu
		(mm)	(mm)	Max	Min	Max	Adet
M10x1,5	CW.07.010	10,0	10,0	4,5	3,0	6,5	50,0
M12x1,5	CW.07.012	12,0	10,0	6,5	4,0	9,0	50,0
M16x1,5	CW.07.016	16,0	12,0	9,0	11,0	13,5	50,0
M20x1,5 s	CW.07.019	20,0	12,0	13,0	15,0	20,0	50,0
M20x1,5	CW.07.020	20,0	12,0	15,0	17,0	22,0	50,0
M20x1,5L	CW.07.021	20,0	12,0	17,0	17,0	22,0	50,0
M25x1,5s	CW.07.024	25,0	12,0	19,0	20,0	27,0	50,0
M25x1,5	CW.07.025	25,0	12,0	19,0	22,0	30,0	50,0
M25x1,5L	CW.07.026	25,0	12,0	22,0	20,0	27,0	25,0
M32x1,5s	CW.07.031	32,0	12,0	26,0	26,0	33,0	25,0
M32x1,5	CW.07.032	32,0	12,0	27,0	28,0	37,0	25,0
M32x1,5L	CW.07.033	32,0	12,0	30,0	28,0	37,0	25,0
M40x1,5s	CW.07.039	40,0	15,0	32,0	31,0	40,0	20,0
M40x1,5	CW.07.040	40,0	15,0	33,0	36,0	45,0	20,0
M40x1,5L	CW.07.041	40,0	15,0	37,0	36,0	45,0	20,0
M50x1,5s	CW.07.049	50,0	15,0	44,0	43,0	54,0	15,0
M50x1,5	CW.07.050	50,0	15,0	45,0	49,0	59,0	15,0

Ürün Özellikleri

Diş normları : PG DIN 46320

: Metrik EN 60423

: NPT ANSI B1.20.1

: GAS ISO 228

Sızdırmazlık : IP 66, IP 68

Isıya dayanımı : -40° C +80° C

Hammadesi : Paslanmaz Çelik 303 304 316 316L



CW Serisi Exproof Zırlı Paslanmaz Kablo Rakorları

Anma Ölçüsü	Kod No	Montaj Çap "Ø"	Diş Boyu	A Kablo Çapı "Ø"	B Kablo Çapı "Ø"		Kutu
		(mm)	(mm)	Max	Min	Max	Adet
PG-7s	CW.07.410	12,5	10,0	4,5	3,0	6,5	50,0
PG-7	CW.07.412	12,5	10,0	6,5	4,0	9,0	50,0
PG-9	CW.07.416	15,5	12,0	9,0	11,0	13,5	50,0
PG-13,5	CW.07.419	20,5	12,0	13,0	15,0	20,0	50,0
PG-16s	CW.07.420	22,5	12,0	15,0	17,0	22,0	50,0
PG-16	CW.07.421	22,5	12,0	17,0	17,0	22,0	50,0
PG-21s	CW.07.424	28,5	12,0	19,0	20,0	27,0	50,0
PG-21	CW.07.425	28,5	12,0	19,0	22,0	30,0	50,0
PG-21L	CW.07.426	28,5	12,0	22,0	20,0	27,0	25,0
PG-29s	CW.07.431	37,5	12,0	26,0	26,0	33,0	25,0
PG-29	CW.07.432	37,5	12,0	27,0	28,0	37,0	25,0
PG-29L	CW.07.433	37,5	12,0	30,0	28,0	37,0	25,0
PG-36s	CW.07.439	47,0	15,0	32,0	31,0	40,0	20,0
PG-36	CW.07.440	47,0	15,0	33,0	36,0	45,0	20,0
PG-36L	CW.07.441	47,0	15,0	37,0	36,0	45,0	20,0
PG-36	CW.07.449	47,0	15,0	44,0	43,0	54,0	15,0
PG-42s	CW.07.450	55,0	15,0	45,0	49,0	59,0	15,0
PG-42	CW.07.451	55,0	15,0	49,0	49,0	59,0	15,0

Ürün Özellikleri

Diş normları : PG DIN 46320

: Metrik EN 60423

: NPT ANSI B1.20.1

: GAS ISO 228

Sızdırmazlık : IP 66, IP 68

Isıya dayanımı : -40° C +80° C

Hammadesi : Paslanmaz Çelik 303 304 316 316L



CW Serisi Exproof Zırlı Paslanmaz Kablo Rakorları

Anma Ölçüsü	Kod No	Montaj Çap "Ø"	Diş Boyu	A Kablo Çapı "Ø"		B Kablo Çapı "Ø"		Kutu
		(mm)	(mm)	Max	Min	Max	Adet	
1/8 Npt	CW.07.210	10,0	16,0	4,5	3,0	6,5	50,0	
1/4" Npt	CW.07.212	13,5	16,0	6,5	4,0	9,0	50,0	
3/8" Npt	CW.07.216	17,0	16,0	9,0	11,0	13,5	50,0	
1/2"s Npt	CW.07.219	21,3	18,0	11,0	11,0	15,0	50,0	
1/2" Npt	CW.07.220	21,3	18,0	13,0	15,0	20,0	50,0	
1/2"L Npt	CW.07.221	21,3	18,0	15,0	17,0	22,0	50,0	
3/4"s Npt	CW.07.224	26,7	18,0	17,0	17,0	22,0	50,0	
3/4" Npt	CW.07.225	26,7	18,0	19,0	20,0	27,0	50,0	
3/4"L Npt	CW.07.226	26,7	18,0	19,0	22,0	30,0	25,0	
1"s Npt	CW.07.231	33,5	20,0	22,0	20,0	27,0	25,0	
1" Npt	CW.07.232	33,5	20,0	26,0	26,0	33,0	25,0	
1"L Npt	CW.07.233	33,5	20,0	27,0	28,0	37,0	25,0	
1-1/4"s Npt	CW.07.239	42,2	20,0	30,0	28,0	37,0	20,0	
1-1/4" Npt	CW.07.240	42,2	20,0	32,0	31,0	40,0	20,0	
1-1/2s Npt	CW.07.241	48,1	20,0	33,0	36,0	45,0	20,0	
1-1/2" Npt	CW.07.249	48,1	20,0	37,0	36,0	45,0	15,0	
2"s Npt	CW.07.250	59,9	20,0	44,0	43,0	54,0	15,0	